

# Building Java Programs

## Chapter 12

### Recursion

A small set of the total slides just to demonstrate –  
this is a more advanced topic (CSE 143)

Subset of the Supplement Lesson slides from: Building Java Programs, Chapter 12  
by Stuart Reges and Marty Stepp (<http://www.buildingjavaprograms.com/>).

# Recursion

- **recursion:** The definition of an operation in terms of itself.
  - Solving a problem using recursion depends on solving smaller occurrences of the same problem.
  
- **recursive programming:** Writing methods that call themselves to solve problems recursively.
  - An equally powerful substitute for *iteration* (loops)
  - Particularly well-suited to solving certain types of problems

# Why learn recursion?

- "cultural experience" - A different way of thinking of problems
- Can solve some kinds of problems better than iteration
- Leads to elegant, simplistic, short code (when used well)
- Many programming languages ("functional" languages such as Scheme, ML, and Haskell) use recursion exclusively (no loops)
- A key component of the rest of our assignments in CSE 143

# Recursion and cases

- Every recursive algorithm involves at least 2 cases:
  - **base case:** A simple occurrence that can be answered directly.
  - **recursive case:** A more complex occurrence of the problem that cannot be directly answered, but can instead be described in terms of smaller occurrences of the same problem.
  - Some recursive algorithms have more than one base or recursive case, but all have at least one of each.
  - A crucial part of recursive programming is identifying these cases.

# Recursion in Java

- Consider the following method to print a line of \* characters:

```
// Prints a line containing the given number of stars.  
// Precondition: n >= 0  
public static void printStars(int n) {  
    for (int i = 0; i < n; i++) {  
        System.out.print("*");  
    }  
    System.out.println();    // end the line of output  
}
```

- Write a recursive version of this method (that calls itself).
  - Solve the problem without using any loops.
  - Hint: Your solution should print just one star at a time.

# A basic case

- What are the cases to consider?
  - What is a very easy number of stars to print without a loop?

```
public static void printStars(int n) {  
    if (n == 1) {  
        // base case; just print one star  
        System.out.println("*");  
    } else {  
        ...  
    }  
}
```

# Handling more cases

- Handling additional cases, with no loops (in a bad way):

```
public static void printStars(int n) {
    if (n == 1) {
        // base case; just print one star
        System.out.println("*");
    } else if (n == 2) {
        System.out.print("*");
        System.out.println("*");
    } else if (n == 3) {
        System.out.print("*");
        System.out.print("*");
        System.out.println("*");
    } else if (n == 4) {
        System.out.print("*");
        System.out.print("*");
        System.out.print("*");
        System.out.println("*");
    } else ...
}
```

# Handling more cases 2

- Taking advantage of the repeated pattern (somewhat better):

```
public static void printStars(int n) {
    if (n == 1) {
        // base case; just print one star
        System.out.println("*");
    } else if (n == 2) {
        System.out.print("*");
        printStars(1);    // prints "*"
    } else if (n == 3) {
        System.out.print("*");
        printStars(2);    // prints "***"
    } else if (n == 4) {
        System.out.print("*");
        printStars(3);    // prints "****"
    } else ...
}
```



# Using recursion properly

- Condensing the recursive cases into a single case:

```
public static void printStars(int n) {  
    if (n == 1) {  
        // base case; just print one star  
        System.out.println("*");  
    } else {  
        // recursive case; print one more star  
        System.out.print("*");  
        printStars(n - 1);  
    }  
}
```

# "Recursion Zen"

- The real, even simpler, base case is an  $n$  of 0, not 1:

```
public static void printStars(int n) {
    if (n == 0) {
        // base case; just end the line of output
        System.out.println();
    } else {
        // recursive case; print one more star
        System.out.print("*");
        printStars(n - 1);
    }
}
```

- **Recursion Zen:** The art of properly identifying the best set of cases for a recursive algorithm and expressing them elegantly.  
(A CSE 143 informal term)

# Recursive tracing

- Consider the following recursive method:

```
public static int mystery(int n) {  
    if (n < 10) {  
        return n;  
    } else {  
        int a = n / 10;  
        int b = n % 10;  
        return mystery(a + b);  
    }  
}
```

- What is the result of the following call?

```
mystery(648)
```

# A recursive trace

mystery(648) :

- `int a = 648 / 10; // 64`
- `int b = 648 % 10; // 8`
- `return mystery(a + b); // mystery(72)`

mystery(72) :

- `int a = 72 / 10; // 7`
- `int b = 72 % 10; // 2`
- `return mystery(a + b); // mystery(9)`

mystery(9) :

- `return 9;`